

AGRI TRAC

UNIVERSAL MOTOR OIL FOR TRACTORS.

DESCRIPTION :

AGRI TRAC is an universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems for tractors.

Viscosity classes : 10W30, 15W30, 15W40 and 20W40.

ADVANTAGES :

Good protection against corrosion.
Good detergent and dispersant properties.
Good resistance against ageing.
Long lifetime.
Only one oil for the lubrication of all tractor parts.

SPECIFICATIONS :

API	CG-4, CF-4, SF/CE	JOHN DEERE	JDM J27
	GL 4, GL 5 (low speed/high torque)	MASSEY FERGUSON	M-1135
MIL	MIL-L-2104 D/C		M-1139
	MIL-L-2105		M-1143
	MIL-L-46152 B		M-1144
ACEA	E3, E2	ZF	TE-ML 06A & B ,07B
CCMC	D4	NEW HOLLAND	NH 330G (15W40)
FORD	ESN-M2C-159 B/C ESN-M2C-134 C/D		NH 030C (10W30) NH 024C (15W40)
MAN	271	CASE NEW HOLLAND	MAT 3525
MB	227.1		MAT 3526

APPLICATIONS :

This multigrade oil is advised for the lubrication of either charged or not charged diesel engines (TURBO), 4-stroke gasoline engines and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines for off-highway equipment.



TYPICAL CHARACTERISTICS AGRI TRAC :

Test	Method	Unit	Average result			
			10W30	15W30	15W40	20W40
SAE-class			10W30	15W30	15W40	20W40
Density at 15°C	D 4052	kg / m ³	881	887	886	890
Viscosity at -25°C	D 5293	cP	6700	-	-	-
Viscosity at -20°C	D 5293	cP	-	6600	6600	-
Viscosity at -15°C	D 5293	cP	-	-	-	6900
Viscosity at 40°C	D 445	cSt	75	81,7	110	115
Viscosity at 100°C	D 445	cSt	11,4	10,8	13,7	14,5
Viscosity index	D 2270		144	118	123	128
Pour point	D 6892	°C	-35	-35	-34	-27
TBN	D 2896	g KOH/kg	10,7	10,7	10,7	10,7
Flash point COC	D 92	°C	216	222	222	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

